



SAFETY DATA SHEET

CLiKZiN Spray-On

Section 1. Identification

Product identifier : CLiKZiN Spray-On
Product code : 124000000181
Other means of identification : A-20086 A; AH2010; CLIKZIN SPRAY-ON SHEEP BLOWFLY TREATMENT

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Veterinary product.
Uses advised against : None known.

Company Name : Elanco Australasia Pty Ltd
106 Wiri Station Road,
Manukau, Auckland 2104, New Zealand

Telephone number : +64 0800 352 626
0800 446 121 (Adverse Events Local Number)

Emergency telephone number : CHEMTREC International: 00 1 703-527-3887 (24 hours)
CHEMTREC: +64 9-801 0034 (Local)
CHEMTREC: 0800 425 459 (Freephone)

Email : elanco_sds@elancoah.com

Section 2. Hazards identification

HSNO Approval Number : HSR100759
HSNO Group Standard : Veterinary Medicines (Non-dispersive Open System Application)
HSNO Classification : SKIN IRRITATION - Category 2
SKIN SENSITISATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 11.9%

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2020 Transport of Dangerous Goods on Land.

GHS label elements

Signal word : Warning
Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Do not apply directly into or onto water.
Take all reasonable steps to ensure that the substance does not cause any significant adverse effects to the environment beyond the application area.
Prevention : P280 - Wear protective gloves.
P273 - Avoid release to the environment.
P260 - Do not breathe vapour.
P264 - Wash thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Section 2. Hazards identification

- Response** : P314 - Get medical advice/attention if you feel unwell.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Symbol** :



Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
propane-1,2-diol	≥10 - ≤30	57-55-6
Dicyclanil	≤3	112636-83-6
Sodium hydroxide > 0.5% aqueous solution	<1	1310-73-2
Methylparaben	<1	99-76-3
Propylparaben	<1	94-13-3
Butylated hydroxytoluene	<1	128-37-0
Acid blue 3	≤1	3536-49-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First aid measures

- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Eye contact** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Inhalation** : No specific data.
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : No specific treatment.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
- Hazchem code** : 3Z
- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Protective measures

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 2 to 30°C (35.6 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
propane-1,2-diol	<p>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2020). WES-TWA: 10 mg/m³ 8 hours. Form: Particulate WES-TWA: 150 ppm 8 hours. Form: Vapor and particulates WES-TWA: 474 mg/m³ 8 hours. Form: Vapor and particulates</p> <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates</p> <p>Safe Work Australia (Australia, 12/2019). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 150 ppm 8 hours. Form: Vapor and particulates TWA: 474 mg/m³ 8 hours. Form: Vapor and particulates</p>
5-Pyrimidinecarbonitrile, 4,6-diamino-2-(cyclopropylamino)- Preparations containing sodium hydroxide. (except for preparations which contain 5% or less of sodium hydroxide)	<p>Elanco OEL (ELANCO). TWA: 50 µg/m³ 8 hours.</p> <p>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2020). WES-Ceiling: 2 mg/m³</p> <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 2 mg/m³ 15 minutes.</p> <p>Safe Work Australia (Australia, 12/2019). PEAK: 2 mg/m³</p>
2,6-di-tert-butyl-p-cresol	<p>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2020). Skin sensitiser. WES-TWA: 10 mg/m³ 8 hours.</p> <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours.</p> <p>Safe Work Australia (Australia, 12/2019). TWA: 10 mg/m³ 8 hours.</p>

Biological exposure indices

No exposure indices known.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid. [Suspension]
- Colour** : Green.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : 5.5 to 7.5
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.
- Flash point** :

Ingredient name	Closed cup			Open cup		
	°C	°F	Method	°C	°F	Method
cyclohexane	-20	-4				
acrylic acid				48.5	119.3	DIN 51755
propane-1,2-diol	99	210.2				
2,6-di-tert-butyl-p-cresol				126.67	260	
Coconut oil	215.85 to 286.85	420.5 to 548.3				
Sorbitan monolaurate, ethoxylated	275	527				

- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Not available.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method

Section 9. Physical and chemical properties and safety characteristics

cyclohexane	93.01	12.4				
water	23.8	3.2				
acrylic acid	2.85	0.38				
propane-1,2-diol	0.15	0.02	EU A.4			
2,6-di-tert-butyl-p-cresol	0.01	0.0013				
propyl 4-hydroxybenzoate	0	0		0	0	

Relative vapour density : Not available.

Relative density : 1 to 1.03

Density : 1 to 1.03 g/cm³

Solubility(ies) :

Media	Result
cold water	Soluble
hot water	Soluble

Solubility in water : Not available.

Miscible with water : Yes.

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
cyclohexane	260	500	
propane-1,2-diol	371	699.8	
acrylic acid	390	734	
methyl 4-hydroxybenzoate	>403	>757.4	

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

- Inhalation** : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : No specific data.
Ingestion : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
redness
Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Dicyclanil	LC50 Inhalation Vapour	Rat	3184 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	520 mg/kg	-
Sodium hydroxide > 0.5% aqueous solution	LD50 Oral	Rat	2000 mg/kg	-
Methylparaben	LD50 Oral	Rat	2100 mg/kg	-
Butylated hydroxytoluene	LD50 Oral	Rat	890 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
propane-1,2-diol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Human	-	168 hours 500 mg	-
	Skin - Mild irritant	Woman	-	96 hours 30 %	-
	Skin - Moderate irritant	Child	-	96 hours 30 % C	-
Sodium hydroxide > 0.5% aqueous solution	Skin - Moderate irritant	Human	-	72 hours 104 mg l	-
	Eyes - Mild irritant	Rabbit	-	400 ug	-
	Eyes - Severe irritant	Monkey	-	24 hours 1 %	-
	Eyes - Severe irritant	Rabbit	-	1 %	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 50 ug	-
	Skin - Mild irritant	Human	-	24 hours 2 %	-
Methylparaben	Skin - Severe irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 0.1 MI	-
Butylated hydroxytoluene	Skin - Moderate irritant	Rabbit	-	504 hours 0.5 MI l	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-

Section 11. Toxicological information

	Skin - Mild irritant	Human	-	mg 48 hours 500	-
	Skin - Moderate irritant	Rabbit	-	mg 48 hours 500 mg	-

Sensitisation

Not available.

Potential chronic health effects

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Eye contact** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Methylparaben	Chronic NOAEL Oral	Rat - Male, Female	250 mg/kg	28 days; days per week

Carcinogenicity

Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Methylparaben	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Animal	Positive

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Dicyclanil	Category 1	-	-

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
CLiKZiN	28104.4	N/A	N/A	528.5	N/A
propane-1,2-diol	20000	20800	N/A	N/A	N/A
Dicyclanil	520	N/A	N/A	11	N/A
Sodium hydroxide > 0.5% aqueous solution	2000	N/A	N/A	N/A	N/A
Methylparaben	2100	N/A	N/A	N/A	N/A
Butylated hydroxytoluene	890	N/A	N/A	N/A	N/A

Section 12. Ecological information

Ecotoxicity : This material is harmful to aquatic life with long lasting effects.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
propane-1,2-diol	EC50 19000 mg/l EC50 34400 mg/l Acute LC50 1020000 µg/l Fresh water	Aquatic plants Daphnia Crustaceans - Ceriodaphnia dubia	72 hours 48 hours 48 hours
5-Pyrimidinecarbonitrile, 4,6-diamino-2-(cyclopropylamino)-	Acute LC50 710000 µg/l Fresh water EC50 1.1 mg/l	Fish - Pimephales promelas Daphnia	96 hours 48 hours
Preparations containing sodium hydroxide. (except for preparations which contain 5% or less of sodium hydroxide)	LC50 60 mg/l NOEC 9.6 mg/l NOEC 0.006 mg/l EC50 34.59 to 47.13 mg/l	Fish Algae Daphnia Daphnia - Ceriodaphnia dubia	96 hours 72 hours 21 days 48 hours
methyl 4-hydroxybenzoate	Acute EC50 40.38 mg/l Fresh water Acute LC50 125 ppm Fresh water EC50 91 mg/l	Crustaceans - Ceriodaphnia dubia - Neonate Fish - Gambusia affinis - Adult Algae - Pseudokirchneriella subcapitata	48 hours 96 hours 72 hours
propyl 4-hydroxybenzoate 2,6-di-tert-butyl-p-cresol	LC50 59.5 mg/l NOEC 0.2 mg/l Acute EC50 11.2 mg/l Fresh water Acute EC50 7 mg/l Fresh water Acute EC50 0.758 mg/l Acute EC50 0.48 mg/l Acute LC50 0.199 mg/l Chronic NOEC 0.15 mg/l	Fish - Oryzias latipes Daphnia - Daphnia magna Daphnia - Daphnia magna Daphnia - Daphnia magna Algae Daphnia - Daphnia magna Fish Crustaceans	96 hours 21 days 48 hours 48 hours 96 hours 48 hours 96 hours 48 hours

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
propane-1,2-diol	OECD 301F Ready Biodegradability - Manometric Respirometry Test	38 % - Not readily - 28 days	-	-
methyl 4-hydroxybenzoate	OECD 301F Ready Biodegradability - Manometric Respirometry Test	92.2 % - 28 days	-	-

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
propane-1,2-diol	-	-	Not readily
methyl 4-hydroxybenzoate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
propane-1,2-diol	-1.07	-	Low
methyl 4-hydroxybenzoate	1.98	-	Low
propyl 4-hydroxybenzoate	3.04	-	Low
2,6-di-tert-butyl-p-cresol	5.1	330 to 1800	High

Mobility in soil







Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	New Zealand - Land - road/ railway	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclanil)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclanil)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclanil)
Transport hazard class(es)	9  	9  	9  
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

Additional information

New Zealand

: **Hazchem code** 3Z

Remarks This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Section 14. Transport information

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

HSNO Approval Number : HSR100759

HSNO Group Standard : Veterinary Medicines (Non-dispersive Open System Application)

HSNO Classification : SKIN IRRITATION - Category 2
SKIN SENSITISATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

ACVM No. : A010284

Inventory list

New Zealand : All components are listed or exempted.

Section 16. Other information

History

Date of issue/Date of revision : 11/23/2023

Date of previous issue : 3/14/2023

Version : 0.03

Key to abbreviations : ADG = Australian Dangerous Goods
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SGG = Segregation Group
UN = United Nations

References : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

As of the date of issuance, we are providing available information relevant to the handling of this material in the workplace. All information contained herein is offered with the good faith belief that it is accurate. THIS SAFETY DATA SHEET SHALL NOT BE DEEMED TO CREATE ANY WARRANTY OF ANY KIND (INCLUDING WARRANTY OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE). In the event of an adverse incident associated with this material, this safety data sheet is not intended to be a substitute for consultation with appropriately trained personnel. Nor is this safety data sheet intended to be a substitute for product literature which may accompany the finished product.

For additional information contact:

Elanco Animal Health

0011+1-877-352-6261

0011+1-800-428-4441